TECHNICAL DATA SHEET

Issue date: 01/02/2026

**Cod. 1088B**
Aluminium handle 150 cm Ø 25 mm - Blue

Lightweight and durable aluminium handle with ergonomic plastic grip, featuring a hole for hanging and a non-slip finish to ensure a secure and comfortable hold. Equipped with Italian thread for use with compatible tools.

## Certifications and regulatory compliance

- Regulation (EC) No 1907/2006 (REACH) and updates
- FDA CFR Title 21 and amendments
- Regulation (EU) No 1935/2004 and amendments
- Regulation (EU) No 10/2011 and amendments
- Regulation (EU) No 2023/2006 (Good Manufacturing Practices GMP) and amendments

## Conditions of use and safety requirements[1]

| | |
|---|---|
| Operating temperature | min -20 / max 80 C° |
| Dishwasher resistance[2] | |
| Steam sterilization | Compatible with autoclave cycles at 121°C for 15 minutes according to ISO 17665-1:2006 |
| Instructions for use | • Remove all packaging and/or labels.<br>• Sanitize/disinfect according to HACCP protocol.<br>• Hang the tool using appropriate hooks/supports.<br>• Allow to dry completely before use. |
| Signs of deterioration | The product must be regularly inspected. Observable signs of deterioration include:<br>• Material softening, breakage, or discoloration;<br>• Detachment of parts or structural damage.<br><br>If any such issues are detected, the product must be withdrawn from food contact use and replaced, as also required under Regulation (EU) 2023/988 on general product safety. |

## Technical specifications

| | | | |
|---|---|---|---|
| Length (mm) | 1500 | Material | PP - AL |
| Width (mm) | 0 | Net weight (kg) | 0,31 |
| Height (mm) | 0 | Quantity per pack (pcs) | 10 |
| Diameter (mm) | 25 | | |

[1] in accordance with Regulations (EU) 2025/351 and 2023/988

[2] Exposure to high temperatures or intensive cycles may cause bristle deformation or material degradation.



IGEAX S.R.L. - Via delle Querce 16 - Z.I. Fenilrosso - 46019, Viadana ( MN) - ITALY - Tel.: +39 0375 780798 - Mail: info@igeax.com